

N-Channel Enhancement Mode Power MOSFET

General Description

The HM75N80 uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. This device is suitable for use in PWM, load switching and general purpose applications.

Features

- $V_{DS}=75V$; $I_D=80A@V_{GS}=10V$;
 $R_{DS(ON)}<8m\Omega @V_{GS}=10V$
- Special process technology for high ESD capability
- Special designed for Convertors and power controls
- High density cell design for ultra low R_{dson}
- Fully characterized Avalanche voltage and current
- Good stability and uniformity with high E_{AS}
- Excellent package for good heat dissipation


Application

- Power switching application
- Hard Switched and High Frequency Circuits
- Uninterruptible Power Supply


Product Summary

BV_{DSS}	typ.	84	V
$R_{DS(ON)}$	typ.	6.5	m Ω
	max.	8.0	m Ω
I_D		80	A

100% UIS TESTED!



TO-220-3L top view



Schematic diagram

Package Marking And Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
HM75N80	HM75N80	TO-220-3L		-	-

Table 1. Absolute Maximum Ratings (TA=25°C)

Parameter	Symbol	Value	Unit
Drain-Source Voltage ($V_{GS}=0V$)	V_{DS}	75	V
Gate-Source Voltage ($V_{DS}=0V$)	V_{GS}	± 25	V
Drain Current (DC) at $T_c=25^\circ C$	$I_{D(DC)}$	80	A
Drain Current (DC) at $T_c=100^\circ C$	$I_{D(DC)}$	60	A
Drain Current-Continuous@ Current-Pulsed (Note 1)	$I_{DM(pluse)}$	320	A
Peak diode recovery voltage	dv/dt	30	V/ns
Maximum Power Dissipation($T_c=25^\circ C$)	P_D	170	W
Derating factor		1.13	W/°C
Single pulse avalanche energy (Note 2)	E_{AS}	580	mJ
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 175	°C

Notes 1.Repetitive Rating: Pulse width limited by maximum junction temperature

2.EAS condition: $T_J=25^\circ C, V_{DD}=50V, V_G=10V, L=0.3mH, I_D=62A$;

Table 2. Thermal Characteristic

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case (Maximum)	R_{thJC}	0.88	$^{\circ}C/W$
Thermal Resistance, Junction-to-Ambient (Maximum)	R_{thJA}	63	$^{\circ}C/W$


Table 3. Electrical Characteristics (TA=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
On/off states						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V I _D =250μA	75	84		V
Zero Gate Voltage Drain Current(Tc=25℃)	I _{DSS}	V _{DS} =75V,V _{GS} =0V			1	μA
Zero Gate Voltage Drain Current(Tc=125℃)	I _{DSS}	V _{DS} =75V,V _{GS} =0V			10	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} =±20V,V _{DS} =0V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} ,I _D =250μA	2	2.85	4	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =40A		6.5	8	mΩ
Dynamic Characteristics						
Forward Transconductance	g _{FS}	V _{DS} =5V,I _D =30A		66		S
Input Capacitance	C _{iss}	V _{DS} =25V,V _{GS} =0V, F=1.0MHz		4400		PF
Output Capacitance	C _{oss}			340		PF
Reverse Transfer Capacitance	C _{rss}			260		PF
Total Gate Charge	Q _g	V _{DS} =30V,I _D =30A, V _{GS} =10V		100		nC
Gate-Source Charge	Q _{gs}			20		nC
Gate-Drain Charge	Q _{gd}			30		nC
Switching times						
Turn-on Delay Time	t _{d(on)}	V _{DD} =30V,I _D =2A,R _L =15Ω V _{GS} =10V,R _G =2.5Ω		17.8		nS
Turn-on Rise Time	t _r			11.8		nS
Turn-Off Delay Time	t _{d(off)}			56		nS
Turn-Off Fall Time	t _f			14.6		nS
Source- Drain Diode Characteristics						
Source-drain current(Body Diode)	I _{SD}				80	A
Pulsed Source-drain current(Body Diode)	I _{SDM}				320	A
Forward on voltage ^(Note 1)	V _{SD}	Tj=25℃,I _{SD} =40A,V _{GS} =0V			1.2	V
Reverse Recovery Time ^(Note 1)	t _{rr}	Tj=25℃,I _F =75A,di/dt=100A/μs			36	nS
Reverse Recovery Charge ^(Note 1)	Q _{rr}				56	nC
Forward Turn-on Time	t _{on}	Intrinsic turn-on time is negligible(turn-on is dominated by L _S +L _D)				


Notes 1. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 1.5\%$, $R_G=25\Omega$, Starting $T_j=25^{\circ}C$

Test circuit


1) E_{AS} test circuits



2) Gate charge test circuit:



3) Switch Time Test Circuit:



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS (curves)

Figure1. Safe operating area




Figure2. Source-Drain Diode Forward Voltage




Figure3. Output characteristics




Figure4. Transfer characteristics




Figure5. Static drain-source on resistance




Figure6. $R_{DS(ON)}$ vs Junction Temperature




Figure7. BV_{DSS} vs Junction Temperature




Figure8. $V_{GS(th)}$ vs Junction Temperature




Figure9. Gate charge waveforms







Figure10. Capacitance



TO-220-3L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	4.470	4.670	0.176	0.184
A1	2.520	2.820	0.099	0.111
b	0.710	0.910	0.028	0.036
b1	1.170	1.370	0.046	0.054
c	0.330	0.650	0.013	0.026
c1	1.200	1.400	0.047	0.055
D	10.010	10.350	0.394	0.407
E	8.500	8.900	0.335	0.350
E1	12.060	12.460	0.475	0.491
e	2.540 (TYP.)		0.100 (TYP.)	
e1	4.980	5.180	0.196	0.204
F	2.590	2.890	0.102	0.114
H	8.440 REF.		0.332 REF.	
h	0.000	0.300	0.000	0.012
L	13.400	13.800	0.528	0.543
L1	3.560	3.960	0.140	0.156
V	6.360 REF.		0.250 REF.	
I	6.300 REF.		0.248 REF.	
Φ	3.735	3.935	0.147	0.155

ATTENTION:

- Any and all H&M SEMI products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your H&M SEMI representative nearest you before using any H&M SEMI products described or contained herein in such applications.
- H&M SEMI assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all H&M SEMI products described or contained herein.
- Specifications of any and all H&M SEMI products described or contained herein stipulate the performance, characteristics, functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- H&M Semiconductor CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all H&M SEMI products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of H&M Semiconductor CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. H&M SEMI believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the H&M SEMI product that you intend to use.
- This catalog provides information as of Mar. 2010. Specifications and information herein are subject to change without notice.