

40V 250mA Ultralow-Quiescent-Current LDO

■ DESCRIPTION

The HM73XXHB ultra-low quiescent current regulator features low dropout voltage and low current in the standby mode. With less than 1.5 μ A quiescent current at no load, the HM73XXHB is ideally suited for standby micro-control-unit systems, especially for always-on applications like E-meters, fire alarms, smoke detectors and other battery operated systems. The HM73XXHB retains all of the features that are common to low dropout regulators including a low dropout PMOS pass device, short circuit protection, and thermal shutdown.

The HM73XXHB has a 40-V maximum operating voltage limit, A -40°C to 125°C operating temperature range, and $\pm 2\%$ output voltage tolerance over the entire output current, input voltage, and temperature range. The HM73XXHB is available in a TO92 through-hole and SOT235, SOT223, SOT893 surface mount packages.


■ FEATURES

- VIN Range up to 40V
- Output Voltage Tolerances of $\pm 2\%$ Over the Temperature Range
- Output Current of 250 mA
- Ultra Low Quiescent Current ($I_Q = 1.2 \mu A$)
- Dropout Voltage Typically 1200 mV at $I_{OUT} = 250 \text{ mA}$
- Internal Thermal Overload Protection
- Internal Short-Circuit Current Limit
- Ceramic Capacitor Stable

■ APPLICATIONS


- E-meters, Water Meters and Gas Meters
- Fire Alarm, Smoke Detector
- Appliances and White Goods

■ Typical Application Circuit




Ceramic Capacitor Stable

■ BLOCK DIAGRAM



■ RECOMMEND PACKAGE TYPE



Pin Name	Pin No. TO92	Pin No. SOT23-5	Pin No. SOT223 SOT89-3	Pin No. SOT223 SOT89-3	Pin Function
VOUT	1	5	3	3	Output Voltage Pin
GND	2	2	2,4	1	Ground
VIN	3	1	1	2,4	Input Voltage pin
EN	--	3	--	--	Enable

■ ABSOLUTE MAXIMUM RATINGS (T_a=25°C,Note)

VIN ----- -0.3V to +45V
 Junction Temperature----- 125°C
 Lead Temperature (Soldering, 10 sec.)----- 300°C
 Storage Temperature ----- -65°C to 150°C

Recommended Operating Conditions

Input Voltage, VIN ----- +2.7V to +40V
 Junction Temperature ----- -40°C to 125°C







■ ELECTRICAL CHARACTERISTICS

$V_{IN}=V_{OUT} + 1V$, $I_{OUT}=1mA$, $C_{IN}=C_{OUT}=2.2\mu F$, $T_J=25^{\circ}C$, unless otherwise specified

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage Range	V_{OUT}		1.5		5.5	V
Output Voltage Accuracy	ΔV_{OUT}		-2		2	%
Line Regulation	ΔV_{LINE}	$V_{IN} = V_{OUT} + 1V$ to 40V		2	12	mV
Load Regulation	ΔV_{LOAD}	$I_{OUT} = 1mA$ to 100mA		3	15	mV
		$I_{OUT} = 1mA$ to 250mA		15	30	
Dropout Voltage	V_{DROP}	$I_{OUT} = 100mA$		400		mV
		$I_{OUT} = 250mA$		1200		mV
Quiescent Current	I_Q	$T_J = 25^{\circ}C$		1.2	2.5	μA
Current Limit	I_{CL}		270	300		mA
Enable high level	V_{ENHI}		0.9			V
Enable low level	V_{ENLO}				0.4	V
Enable pin pull high current	I_{EN}			0.3		μA
Power-supply rejection ratio	PSRR	$f = 1kHz$		80		dB
		$f = 10kHz$		60		dB

TYPICAL CHARACTERISTICS

$V_{IN}=V_{OUT} + 1V$, $I_{OUT}=1mA$, $V_{OUT}=3.3V$, $C_{IN}=C_{OUT}=1\mu F$, $T_J=25^{\circ}C$, unless otherwise specified



■ TYPICAL CHARACTERISTICS

$V_{IN}=V_{OUT} + 1V$, $I_{OUT}=1mA$, $V_{OUT}=3.3V$, $C_{IN}=C_{OUT}=1\mu F$, $T_J=25^{\circ}C$, unless otherwise specified




Fig 7 Vout Load Transient (50 to 250mA)




Fig 8 Vout Short to GND




Fig 9 Vin Start up